


## BTD-Series

The BTD-Series combines state-of-the-art design, easy handling, extensive equipment and brilliant weighing results delivered by using the revolutionary UNIBLOC-weighing system, to a unique standard balance.

### BTD - Series

- calibration per push on the CAL-button with an external calibration weight
- separate stability indication
- RS 232 interface
- huge weighing chamber with glass wind protection as standard (mg-balances)
- fast and convenient handling with the new menu operating key
- direct data transfer into Windows application by Windows direct function
- various application programs (e. g. formulation, counting, %)
- new backlit display for more comfortable readings
- 5 years warranty
- many models EU verified on demand



BTD-3202

Technical data	Accuracy	Capacity	Pan size	Calibration	Measuring	EU verification
BTD-423	0,001 g	420 g	110 mm	extern	<b>Time</b>	no
BTD-423V	0,001 g	420 g	110 mm	extern	2 sec	yes
BTD-323	0,001 g	320 g	110 mm	extern	2 sec	no
BTD-323V	0,001 g	320 g	110 mm	extern	2 sec	yes
BTD-223	0,001 g	220 g	110 mm	extern	2 sec	no
BTD-223V	0,001 g	220 g	110 mm	extern	2 sec	yes
BTD-4202	0,01 g	4200 g	167 x 181 mm	extern	2 sec	no
BTD-4202V	0,01 g	4200 g	167 x 181 mm	extern	2 sec	yes
BTD-3202	0,01 g	3200 g	167 x 181 mm	extern	2 sec	no
BTD-3202V	0,01 g	3200 g	167 x 181 mm	extern	2 sec	yes
BTD-2202	0,01 g	2200 g	167 x 181 mm	extern	2 sec	no
BTD-2202V	0,01 g	2200 g	167 x 181 mm	extern	2 sec	yes